



3 Form

- E mit Gewinde-Sackloch
- D mit Gewinde-Durchloch

1		2			2							
d ₁	d ₂ Form E			d ₃ Form D			d ₄	b	h	t ₁ min.	t ₂	
20	M 4	-	-	-	-	-	-	9,5	11	6	-	
26	M 5	M 6	-	-	-	-	-	11	13	6	-	
32	M 5	M 6	M 8	M 5	M 6	-	6,5	13	15	6	12	
40	M 5	M 6	M 8	M 5	M 6	M 8	9	15,5	17	6	12	
48	M 8	-	-	M 8	-	-	9	19	19	10	16	
56	M 10	-	-	M 10	-	-	11	21	23	13	20	

Ausführung

- Kunststoff
Thermoplast (Polyamid PA)
- glasfaserverstärkt
- temperaturbeständig bis 130 °C
- schwarz, matt
- Buchse
Messing
- *Kunststoff-Eigenschaften* → Seite 2158
- RoHS

Hinweis

- siehe auch...
- *Flügelmuttern GN 532.1 (mit vorstehender Nabe)* → Seite 616
 - *Flügelmuttern GN 634* → Seite 606
 - *Flügelmuttern GN 640* → Seite 612

Bestellbeispiel

GN 532-40-M8-E

- 1 d₁
- 2 d₂ (d₃)
- 3 Form